

6 ZONE DOOR FRAME METAL DETECTORS



Technical Specification:

- No. of Zones: 6 Zones
- Operational Frequencies: Factory Set/User Selectable
- Sensitivity: 0 to 255(optional 0 to 100)
- Zone Sensitivity: All zones individually settable
- Metal Detection: Ferrous, Non Ferrous metal alloys
- Alarm Signal: Audio-Visual indications
- LED Indicators: Both Front & Back Panels
- Walk Stop indicators: Provided
- Intelligent Digital Counter: Available with information on IN, OUT, NET, ALARM
- Power Supply: Electric current: AC 220v/50 Hz
- Power: Less than 35W
- Battery Backup: Up to 8 hrs.(Optional)
- Calibration: Auto Calibration

- Display Unit: Provided
- Cordless Remote Control: Provided for all setting
- Dimension approx.: Outside: 2200x800x500mm, Inside: 2010x700x500mm
- Weight: 60Kg
- Working Environment: -10°C~55°C
- Usage Area: Mall, Factory, Airport, Office, Hotel, Events, Metro

Detection Area:

According to the basic structure of the human body, the detector is divided into six overlapping regions.

Display:

Both audio alarms and LED visual indications on panels.

Sensitivity:

Each zone sensitivity is settable as per needs.

Appearance:

Rich aesthetic appearance to match the decorum of the surrounding area. Optional panel colors available at extra cost.

Security Protection:

Password protected. Only authorized persons can change the settings.

Safety:

Safe for heart pacemaker users, pregnant women, floppy disks, files, and video tapes.