

MODEL- CO-IP-JH4WG

IP 4MP BULLET CAMERA (COLOURVIEW)



Features:

1. 1/3" 4MP CMOS sensor
2. Support H.264, H.265, MJPEG ;
3. Support Three stream. Main stream: 2592*1520/2304*1296/1920*1080 /1280*960/1280*720 ; Sub stream: 704*576 / 640*360 / 352*288 ; Tri stream: 704*576 / 640*360 / 352*288
4. Support D-WDR, 3D NR, BLC, Auto-white balance for different environments;
5. Support ONVIF, can connect with other company's NVR;
6. ICR switching to surveillance 24 hours;
7. Support image shutter, 4 Shutter area can be set;
8. Support audio input;
9. Support motion detection, motion detection alarm can be sent to email automatically;
10. Support OSD setting and network timing;
11. Support OSD position setting, and internet timing
12. Support mobile surveillance (iOS, android), Web and VMS;
13. Support self-maintenance;
14. IR distance – 30 m

TECHNICAL SPECIFICATION

| | |
|---------------------|--|
| Image Sensor | 4MP 1/3" CMOS Image sensor |
| D/N | Support D/N switching(IR-CUT optional) |
| Shutter | 1/25-1/10000 |
| White Balance | Support automatic white balance |
| BLC | Support |
| Noise Reduction | Support 3D NR |
| WDR | Support D-WDR |
| Motion Detection | Support motion detection |
| Mirror | Support |
| Privacy Shelter | Support 4 Areas |
| OSD | Support OSD setting, drag the position freely |
| Restart | Support |
| Compression | H.264 ,H.265,MJPEG |
| Resolution | Main stream:2594*1520/2304*1296/1920*1080 /960*1080/ 1280*720P ,Sub stream : 704*576 / 640*360 / 352*288 |
| Video Frame Rate | 25fps(50HZ), 25fps(60HZ) |
| Video Adjustment | Brightness, saturability, chroma, contrast, sharpness adjustment |
| Ethernet | RJ-45 10M/100M |
| Wireless | No |
| Network protocol | HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP |

| | |
|-----------------|--|
| | Search(Support P6S IP camera, DVR, NVS and etc.) |
| Access protocol | Support ONVIF/private protocol/CGI |
| Max user qty | 8 |
| Client | iPhone, iPad, Android, Windows |
| Audio | G.711U |
| Audio Input | 1CH input |
| Audio Output | 1CH/OPTIONAL |
| IR Range | 30 m |
| Temperature | -30°C~+60°C |
| Power supply | DC12V 2A |