

MODEL- CO-9797
IP 4MP DOME CAMERA



Features:

1. 1/3" 4MP CMOS sensor
2. Support H.264, H.265, MJPEG ;
3. Support Three stream. Main stream: 2592*1520/2304*1296/1920*1080 /1280*960/
1280*720 ; Sub stream: 704*576 / 640*360 / 352*288 ; Tri stream: 704*576 /
640*360 / 352*288
4. Support D-WDR, 3D NR, BLC, Auto-white balance for different environments;
5. Support ONVIF, can connect with other company's NVR;
6. ICR switching to surveillance 24 hours;
7. Support image shutter, 4 Shutter area can be set;
8. Support audio input;
9. Support motion detection, motion detection alarm can be sent to email automatically;
10. Support OSD setting and network timing;
11. Support OSD position setting, and internet timing
12. Support mobile surveillance (iOS, android), Web and VMS;
13. Support self-maintenance;
14. IR distance – 30 m

TECHNICAL SPECIFICATION

Image Sensor	4MP 1/3" CMOS Image sensor
D/N	Support D/N switching(IR-CUT optional)
Shutter	1/25-1/10000
White Balance	Support automatic white balance
BLC	Support
Noise Reduction	Support 3D NR
WDR	Support D-WDR
Motion Detection	Support motion detection
Mirror	Support
Privacy Shelter	Support 4 Areas
OSD	Support OSD setting, drag the position freely
Restart	Support
Compression	H.264 ,H.265,MJPEG
Resolution	Main stream:2594*1520/2304*1296/1920*1080 /960*1080/ 1280*720P ,Sub stream : 704*576 / 640*360 / 352*288
Video Frame Rate	25fps(50HZ), 25fps(60HZ)
Video Adjustment	Brightness, saturability, chroma, contrast, sharpness adjustment
Ethernet	RJ-45 10M/100M
Wireless	No
Network protocol	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP

	Search(Support P6S IP camera, DVR, NVS and etc.)
Access protocol	Support ONVIF/private protocol/CGI
Max user qty	8
Client	iPhone, iPad, Android, Windows
Audio	G.711U
Audio Input	1CH input
Audio Output	1CH/OPTIONAL
IR Range	30 m
Temperature	-30°C~+60°C
Power supply	DC12V 2A, PoE