



**Model No.-CO-IP-7070**

## **IP 5MP BULLET VARIFOCAL CAMERA**



### **H.265 IP 5MP OUTDOOR CAMERA**

1. 1/2.8" 5MP CMOS Image Sensor

2. Support H264, H.265

3. Support triple stream,

Main stream: 2560\*1920/2560\*1440/2304\*1296/1920\*1080 /1280\*720

Sub-stream 1 : 448P (800\*488)/704\*576/ 704\*576/640\*360 /352\*288 ;

Sub-stream 2 : 640\*360/352\*288

4. Support D-WDR, 3D-NR, BLC, Auto-White balance for different environments.

5. Support ONVIF, can connect with other company's NVR ;

6. ICR switching to surveille 24 hours.



7. Support image shutter, 4 Shutter areas can be set ;
8. Support audio input
9. Support motion detection, motion detection alarm can be sent to email automatically
10. Support OSD setting and network timing
11. Support mobile surveillance (iOS, android), Web and VMS
12. Support self-maintenance
13. Can support POE power (Optional)
14. Support FTP function

## **TECHNICAL SPECIFICATION**

Image Sensor	5MP 1/2.8" sensor
D/N	Support D/N switching(IR-CUT optional)
Shutter	1/25-1/10000
White Balance	Support automatic white balance
WLC	Support
Noise Reduction	Support 3D NR
WDR	Support D-WDR
Motion Detection	Support motion detection
Mirror	Support
Privacy Shelter	Support 4 Areas
OSD	Support OSD setting, drag the position freely
Lens	2.8-12 mm



Compression	H.264 ,H.265
Resolution	Main stream: 2560*1920 /2560*1440/2304*1296 /1920*1080/ 1280*720
Video Frame Rate	25fps 50HZ, 25fps 60HZ
Video Adjustment	Brightness, saturability, chroma, contrast, sharpness adjustment
Ethernet	RJ-45 10M/100M
Wireless	No
Network protocol	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, IP Search(Support P6S IPcamera, DVR, NVS and etc.)
Access protocol	Support ONVIF/private protocol/HK Private Protocol
Max user qty	4
Client	iPhone, iPad, Android, Windows
Audio	G.711U
Audio Input	1CH input
Audio Output	1CH/OPTIONAL
Size	38x38 single board
Temperature	-20°C~+45°C
Power supply	DC12V 2A, PoE