

CO-YPM-Tele-01
Portable Emergency Lighting system



Specifications:

- Type of Lamp/ Wattage; LED 24 Nos
- LED Portable with rated Power: 72W
- Input Voltage: 12v Dc
- Type of housing Material: ABS/ Aluminum alloy
- Color Temperature (degree K): 6000-7000k
- Lens Material: Pc
- Tripod Material: Aluminum
- Battery Working Time: Strong: 4.5h / Middle: 8h / Low 15h
- Battery Charging Time: About 5.5 Hours
- Life Span: 50,000H
- Telescopic Mast Height: Extendable Up to 102cm
- Waterproof: IP 65
- Weight: 8.380 Kgs Approx. (including Battery)
- Low Battery Warning: Intermittent Blinking
- Accessories: Adapter, Car Adapter, Light Cover, Allen Key
- Operating rang: up to 1500 mtr
- 12 x10AH Optionally available in Li battery.
- 4 Modes Operations: Low Bright, Medium Bright, High Bright & SOS
- 5000 lumens power, IP 65.



- **Rated brightness: 5000lm**
- **Charging Time: 5.5H**
- **Running Time: 15H(Low) / 8H(Mid) / 4.5H(High)**
- **Mass Height: 102CM**
- **Battery: Rechargeable Lithium**
- **Spot to Flood in 1 Second**
- **Design to meet IP×5**
- **Easy to install (Installation steps see next page)**
- **Application: Emergency, Maintenance, Police, Rescue, Fire-fighting, Mining**



Installation steps

1. Put out the light and parts. Pull up the pole & adjust the light head on the telescopic pole.
2. Plug the connector between light head and case.
3. Pull up the rod and put it into the corresponding hole.
4. Press the white rubber switch to turn on the light. The light brightness can be adjustable in low / middle/high/sos.
5. Have one 12V socket (charging port, open the Rubber plug to recharge), can supply power for other 12V lamp.
6. Up and down the cover of head, change spot to flood

