

## MODEL- CO-8032E-LME (5mp 32ch DVR)



### Features:

- Support 32ch 5M-N unreal-time encoding;
- Support AHD, TVI, CVI, CVBS, IP video input;
- HDMI/VGA simultaneous video output;
- BIG 1U Case, 2 SATA (Up to 8TB);
- 1\*10/100/1000Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control

	<b>Model</b>	<b>ADVR8032E-LME</b>	
System	processor	HI3531D	
Video	Codec	H.265/H.264	
	preview	32ch 4M-N@15fps(6 in 1)/32ch 5M-N@12fps(6 in 1)/32ch 1080N(6 in 1),default 4M-N	
	Encode	32ch 4M-N@8fps(6 in 1)/32ch 5M-N@6fps(6 in 1)/32ch 1080N@15fps(6 in 1),default 4M-N	
	Decode	16ch 4M-N@8fps(6 in 1)/8ch 5M-N@6fps(6 in 1)/16ch 1080N@15fps(6 in 1),default 4M-N	
	Multi-mode		Analog:32ch 4M-N/32ch 5M-N/32ch 1080N;
			Digital to analog conversion: support
			IP: 32ch 1080P/8ch 3M/4ch 5M
	Playback	16/8ch	
Audio	Compression	G.711a	
	Intercom	Support	
Management	Record mode	Manual>Alarm>Motion detection>Timing	
	Inquire mode	Inquire by Time/Calendar/Event/Channel	
	Storage mode	HDD Storage, Network Storage	
	Backup	Network, USB, SATA	
Interface	Video input	32*BNC (Support Coaxitron)	
	HDMI output	1*HDMI (MAX:1080P)	
	VGA output	1*VGA (MAX:1080P)	

	Audio I/O	16/1
	Alarm I/O	8/1
	Ethernet port	1*10/100/1000Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485,1↑RS232; Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
	HDD	2*SATA interface (Up to 8TB)
General	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/4A
	Consumption	<10W (Without HDD)
	Weight	Around 3KG
	Dimension	440mm(L)* 290mm(W)* 50mm(H)