

CO-120 & C8/160 & D8 WATT **EMERGENCY SOLAR SMART FLOOD LIGHT**



Specification:

- Led: 280/430
- Wattage of lamp (Watt) 120/160 Watt
- Operating rang: up to 1000 mtr
- Operation Mode: High/Low/Bottom of the light led,
5Led in Red Flashing and
5Led in Blue Flashing
- Type of battery: Lithium ion
- Battery Voltage & Capacity: 3.7V & 8x2000 mAH/ as per user requirement.
- Battery Charging time: 8-10 hrs.
- Type of housing Material: aluminum body
- Rugged, impact and water resistant material of housing
- Weight:1.2 kg (with Battery)
- IP Rating: IP66
- Protection against reverse polarity, Protection against battery overcharged,
- Battery status indicator
- Toughened Glass.
- Microcontroller Based.
- Coverage Area 500 to 600 Sq. Ft.
- Charging Voltage: 180 To 270 VAC, 50 Hz.
- Light Radiation Angle – 110o or More.
- Battery Protections provided for over charge, Deep Discharge & Short Circuit.
- Heavy Duty Tripod stand expandable up to 6 feet.
- Material of Tripod stand: Mild steel.
- Can be mount 2 number of flood light at a time.
- Addition specification: provision for Hooter for emergency purpose
- All the accessories come in a heavy duty trolley suit case.
- Mobile phone Charging Facility
- Sturdy carry handle with base stand

