

CO-25W/40W/60W/100W/200W
RECHARGEABLE PORTABLE FLOOD LIGHT



Specification:

- Led: 42/72/88/208/
- Wattage of lamp (Watt) 25/40/60/100/200 Watt
- Operating rang: up to 1000 mtr
- 2 Mode Operation: Full Bright/ Medium Bright
- Type of battery: Lithium ion
- Battery Voltage & Capacity: 3.7V & 6600/8800/11000/12000 mA/ as per user requirement.
- Battery Charging time: 8-10 hrs.
- Type of housing Material: aluminum body
- Continuous search light operation time: Minimum 4-5 hours.
- Rugged, impact and water resistant material of housing
- Weight: 1.2/1.7/2.0/2.67/3.0 kg (with Battery)
- IP Rating: IP66
- Protection against reverse polarity, Protection against battery overcharged,
- Battery status indicator
- Toughened Glass.
- Microcontroller Based.
- Charging Voltage: 180 To 270 VAC, 50 Hz.
- Light Radiation Angle – 110o or More.
- Battery Protections provided for over charge, Deep Discharge & Short Circuit.
- Heavy Duty Tripod stand expandable up to 6 feet.
- Material of Tripod stand: Mild steel.
- Can be mount 2 number of flood light at a time.
- Addition specification: provision for Hooter for emergency purpose
- All the accessories come in a heavy duty trolley suit case.
- Mobile phone Charging Facility
- Sturdy carry handle with base stand
- Provision for solar panel